



ZEBRINO SILVER

MATERIAL
MARBLE

PETROGRAPHIC DENOMINATION
SCHISTOSE MARBLE

LUXURIOUSNESS
MEDIUM - HIGH

A medium-fine grained lithotype with alternating parallel veins that are greenish, brown, white, grey and bluish in color, and vary in thickness from submillimetric for the darker laminas to centimetric for the lighter ones. The material is compact and non-porous.

The Zebrino is a the very classic marble quarried from the Apuan Alps; its pattern is moreover very modern, clean and minimal, reflecting the latest design and desire of elongate combined to simplicity.

APPLICATIONS
INTERIORS
VANITY TOPS
COUNTERTOPS

TEST	STD.	UNITS	CONDITIONING	AVG. VALUE	STD. DEV.
Water Absorption at atmospheric pressure	EN 13755	%	-	0,13	0,01
Apparent Density	EN 1936	Kg/m3	-	2720	5,5
Open Porosity	EN 1936	%	-	0,5	0,24
Flexural Strength under concentrated load	EN 12372	MPa	Dry	20,9	1,5
Flexural Strength under concentrated load	EN 12372	MPa	After 48 cycles of frost	16,8	1,2
Compressive Strength	EN 1926	MPa	-	72,7	9,1
Slip Resistance Honed grade 220	EN 14231	SRV	Dry	51	5
Slip Resistance Honed grade 220	EN 14231	SRV	Wet	24	3

** The values reported are average ones. As the material is natural, we advise to perform new tests according to the your project requirement.*